

TEGOAMIN® 100

TEGOAMIN® 100 is used as a powerful amine activator in the polyurethane foam industry.

Physical properties

Triethylene diamine or 1,4-diazaicyclo-(2,2,2)-octane	
Appearance	white, hygroscopic crystals
Odour	mild, ammoniacal
Purity	99 % min.

Instructions for storage

For TEGOAMIN® 100 we guarantee a shelf life of at least 12 months upon delivery.

TEGOAMIN® 100 should be stored in a dry place at temperatures below 40 °C. Always make sure that the containers are carefully sealed. This is of particular importance as TEGOAMIN® 100 is strongly hygroscopic and may absorb acid vapors.

Safety Instructions

When working with TEGOAMIN® 100 good ventilation of the working areas must be ensured in order to avoid inhalation of vapors. Avoid direct skin contact. Appropriate protective clothing (safety goggles, gloves, special shoes) should be worn. If in spite of all these protective measures direct skin or eye contact with the product did occur, immediately rinse thoroughly with a great amount of water as a first measure.

Packaging

400 kg pallet (16 x 25 kg in cardboard drums)

For Information

- on classification and labelling in accordance with shipping instructions and the Toxic Substances Control Act
- on protective measures during storage and handling
- on measures in case of accidents and fire
- on toxicology and ecological toxicity

please refer to our safety data sheets.

Legal References

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

07/2010

Evonik Industries AG Goldschmidtstraße 100 45127 Essen/Germany
Phone +49 201 173-2466, Fax +49 201 173-1991
polyurethane@evonik.com, www.evonik.com/polyurethane-additives