

TEGOAMIN® B 75

TEGOAMIN® B 75 is a mixture of 75 % TEGOAMIN® 33 and 25 % TEGOAMIN® BDE which is well-proved in the application of polyether polyurethane foam. The product can equally be used for the production of conventional flexible foam and HR foam.

Physical properties

Density (20 °C)	0.997 g/cm ³
Viscosity (20 °C)	50 mPas
Flash point (EN 22719)	79 °C
Solidification point (DIN ISO 301)	-44 °C

Application

Thanks to its components TEGOAMIN® B 75 is equally suitable for the polyurethane block and molded foam technique. Well-balanced catalysis

of the blowing and the cross-linking reaction makes it universally applicable for catalyzing block foams of low densities as well as high densities without impairing the processing latitude.

Instructions for storage

For TEGOAMIN® B 75 we guarantee a shelf life of at least 12 months upon delivery.

Packaging

450 kg pallet (9 x 50 kg in steel drums)
760 kg pallet (4 x 190 kg in steel drums)
950 kg plastic container

Information concerning

- classification and labelling according to regulations for transport of chemicals
- protective measures for storage and handling
- measures in case of accidents and fires
- toxicity and ecological effects

is given in our material safety data sheets

Legal References

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

07/2010

Evonik Industries AG Goldschmidtstraße 100 45127 Essen/Germany
Phone +49 201 173-2466, Fax +49 201 173-1991
polyurethane@evonik.com, www.evonik.com/polyurethane-additives